

# Liebherr-Lubricants

Page: 1/10

## Safety data sheet

according to 1907/2006/EC, Article 31 and 453/2010/EC respectively

Printing date: 23.04.2015

\*\*Version number 2

Revision: 22.04.2015

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **Liebherr Hydraulic-Gear ATF**

**Application / Use:** Motor vehicle lubricant

**Article number:**

Set-number MSDS:

18009

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against:

**Application of the substance / the preparation:** Automotive gear oil

**Uses advised against:** No further relevant information available.

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:**

LIEBHERR-LOGISTICS GmbH

St. Vitus 1

D - 88457 Kirchdorf an der Iller

LIEBHERR-COMPONENTS BIBERACH GmbH

Hans-Liebherr-Strasse 45

D - 88400 Biberach an der Riß

LIEBHERR-WERK BIBERACH GmbH

Memminger Straße 120

D - 88400 Biberach an der Riß

LIEBHERR-WERK EHINGEN GmbH

Dr.-Hans-Liebherr-Strasse 1

D - 89584 Ehingen

LIEBHERR-MISCHTECHNIK GmbH

Im Elchgrund 12

D - 88427 Bad Schussenried

LIEBHERR-MINING EQUIPMENT COLMAR SAS

49 rue Frédéric Hartmann

CS 50038

F - 68025 Colmar Cedex

LIEBHERR-WERK NENZING GmbH

Dr.-Hans-Liebherr-Strasse 1

A - 6710 Nenzing

#### Further information obtainable from:

Liebherr-Lubricant-Hotline: +49 (0) 73 54 / 80-6060

email: [lubricants@liebherr.com](mailto:lubricants@liebherr.com)

#### 1.4 Emergency telephone number:

In case of emergency ONLY:

During working hours (CET): + 49 (0) 73 54 / 80-6060

Emergency response (24 hours) CHEMTREC:

(Contd. on page 2)

GB

# LIEBHERR

# Liebherr-Lubricants

Page: 2/10

## Safety data sheet

according to 1907/2006/EC, Article 31 and 453/2010/EC respectively

Printing date: 23.04.2015

\*\*Version number 2

Revision: 22.04.2015

Trade name: **Liebherr Hydraulic-Gear ATF**

(Contd. of page 1)

+1-703-527-3887  
+44-870-8200418 (United Kingdom)  
+31-858880596 (Netherlands)  
0-800-983-611 (South Africa)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictograms Void

Signal word Void

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local regulations.

Additional information:

EUH208 Contains Amine ethoxylated, Hydrocarbyl sulphide substituted. May produce an allergic reaction.

#### 2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixture

Description: Mixture

#### Dangerous components:

	Mineral oil, viscosity <20.5 mm <sup>2</sup> /s at 40 °C ***) Asp. Tox. 1, H304	50-100%
CAS: 25307-17-9 EINECS: 246-807-3	Amine ethoxylated Skin Corr. 1B, H314; Aquatic Acute 1, H400 (M=10); Acute Tox. 4, H302; Skin Sens. 1, H317	≤0.5%
CAS: 67124-09-8 EINECS: 266-582-5	Hydrocarbyl sulphide substituted Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	≤0.5%

Additional information:

\*\*\*) may contain: CAS-numbers (REACH-Registration numbers):

64742-53-6 (01-2119480375-34), 64742-54-7 (01-2119484627-25), 64742-55-8 (01-2119487077-29), 64742-56-9 (01-2119480132-48), 64742-

(Contd. on page 3)

GB

# LIEBHERR

# Liebherr-Lubricants

Page: 3/10

## Safety data sheet

according to 1907/2006/EC, Article 31 and 453/2010/EC respectively

Printing date: 23.04.2015

\*\*Version number 2

Revision: 22.04.2015

Trade name: **Liebherr Hydraulic-Gear ATF**

(Contd. of page 2)

65-0 (01-2119471299-27), 68037-01-4 (01-2119486452-34), 72623-86-0 (01-2119474878-16), 72623-87-1 (01-2119474889-13), 8042-47-5 (01-2119487078-27), 848301-69-9 (01-0000020164-80), 848301-69-9 (01-0000020163-82)

The wording of the hazard symbols and R-phrases is specified in section 16 if dangerous ingredients are mentioned.

Components with threshold limit values are mentioned at section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General information:

Take affected persons out into the fresh air.

Position and transport stably in side position.

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:** Rinse opened eye for several minutes under running water.

**After swallowing:** Do not induce vomiting; call for medical help immediately.

**4.2 Most important symptoms and effects, both acute and delayed:** No further relevant information available.

**Information for doctor:** Treat symptomatically.

**4.3 Indication of any immediate medical attention and special treatment needed:** No further relevant information available.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing agents:

CO<sub>2</sub>, sand, extinguishing powder.

Use fire extinguishing methods suitable to surrounding conditions.

**For safety reasons unsuitable extinguishing agents:** Do not use water with full jet.

#### 5.2 Special hazards arising from the substance or mixture:

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide (CO)

Sulphur oxide (SO<sub>x</sub>)

#### 5.3 Advice for firefighters

##### Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

**Additional information:** Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

GB

(Contd. on page 4)

# LIEBHERR

# Liebherr-Lubricants

Page: 4/10

## Safety data sheet

according to 1907/2006/EC, Article 31 and 453/2010/EC respectively

Printing date: 23.04.2015

\*\*Version number 2

Revision: 22.04.2015

Trade name: **Liebherr Hydraulic-Gear ATF**

(Contd. of page 3)

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

Wear protective clothing.

#### 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers, surface or ground water.

Prevent from spreading (e.g. by damming-in or oil barriers).

#### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

#### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

**7.1 Precautions for safe handling** Store in cool, dry place in tightly closed receptacles.

**Handling:** When handling product in drums use safety footwear and suitable tools. At work please do not eat, drink or smoke.

**Information about fire - and explosion protection:** Fire class DIN EN 2: B

#### 7.2 Conditions for safe storage, including any incompatibilities

**Storage:**

**Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

Provide floor trough without outlet.

Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

**Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidising agents.

Store away from water.

**Further information about storage conditions:** Recommended storage temperature: 5 to 40 °C

**Shelf life from date of dispatch:** 5 years (at proper storage)

**7.3 Specific end use(s):** For more information see technical information.

### SECTION 8: Exposure controls/personal protection

**Additional information about design of technical facilities:** No further data; see section 7.

(Contd. on page 5)

GB

# LIEBHERR

# Liebherr-Lubricants

Page: 5/10

## Safety data sheet

according to 1907/2006/EC, Article 31 and 453/2010/EC respectively

Printing date: 23.04.2015

\*\*Version number 2

Revision: 22.04.2015

Trade name: **Liebherr Hydraulic-Gear ATF**

(Contd. of page 4)

### 8.1 Control parameters

**Ingredients with limit values that require monitoring at the workplace:**

**Additional Occupational Exposure Limit Values for possible hazards during processing:** TLV-TWA oil mist 5 mg/m<sup>3</sup>

**Additional information:**

The lists valid during the making were used as basis.

If formation of steam, mist or aerosols take place the concentration in the air has to be kept at the lowest possible level.

### 8.2 Exposure controls

**Personal protective equipment:**

**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Avoid close or long term contact with the skin.

**Respiratory protection:**

No respiratory protection is ordinarily required under normal conditions of use. Select a filter suitable for combined particulate/ gases and organic vapours (boiling point > 65 °C, EN 14387), if exposure limit is exceeded or when aerosol or mist is formed.

**Protection of hands:**

Safety gloves of nitrile rubber or viton.

Preventive skin protection by use of skin-protecting agents is recommended.

**Material of gloves**

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material:**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Value for the permeation: Level = 6 (480 min)

**Eye protection:** Goggles recommended during refilling.

**Body protection:** Protective work clothing.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**General Information**

**Appearance:**

**Form:** Fluid

**Colour:** Red

**Odour:** Mild

**Odour threshold:** Not determined.

**pH-value:** Not determined.

(Contd. on page 6)

GB

# LIEBHERR

# Liebherr-Lubricants

Page: 6/10

## Safety data sheet

according to 1907/2006/EC, Article 31 and 453/2010/EC respectively

Printing date: 23.04.2015

\*\*Version number 2

Revision: 22.04.2015

Trade name: **Liebherr Hydraulic-Gear ATF**

(Contd. of page 5)

<b>Change in condition</b>	
Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	Undetermined.
Drip point:	Not determined.
<b>Flash point:</b>	180 °C (DIN ISO 2592)
<b>Flammability (solid, gaseous):</b>	Not applicable.
<b>Ignition temperature:</b>	Not applicable.
<b>Decomposition temperature:</b>	Not determined.
<b>Self-igniting:</b>	> 320 °C
<b>Danger of explosion:</b>	The product shows no danger of explosion, but it may build explosive mixtures with air (by vaporisation, oil mist formation, heating above the flash point).
<b>Explosion limits:</b>	
Lower:	1.0 Vol % (typ.)
Upper:	10 Vol % (typ.)
<b>Vapour pressure:</b>	Not determined.
<b>Density at 15 °C:</b>	0.877 g/cm <sup>3</sup> (DIN 51 757)
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>Evaporation rate</b>	Not determined.
<b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
<b>Partition coefficient (n-octanol/water):</b>	> 6
<b>Viscosity:</b>	
Kinematic at 40 °C:	39 mm <sup>2</sup> /s (DIN 51 562)
<b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

10.1 Reactivity See 10.2 to 10.6

10.2 Chemical stability: Stable at normal conditions.

Thermal decomposition / conditions to be avoided: Avoid contact with heat, sparks, flames and all other sources of ignition.

10.3 Possibility of hazardous reactions: Reacts with strong oxidising agents.

10.4 Conditions to avoid No specific data available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

GB

# LIEBHERR

# Liebherr-Lubricants

Page: 7/10

## Safety data sheet

according to 1907/2006/EC, Article 31 and 453/2010/EC respectively

Printing date: 23.04.2015

\*\*Version number 2

Revision: 22.04.2015

Trade name: **Liebherr Hydraulic-Gear ATF**

(Contd. of page 6)

**Additional information:** Product is not classified as inflammable but can burn.

### SECTION 11: Toxicological information

**11.1 Information on toxicological effects** These statements are based on data for components of the material or for similar materials.

**Acute toxicity:**

**LD/LC50 values relevant for classification:**

Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	> 5000 mg/kg (rabbit)

**25307-17-9 Amine ethoxylated**

Oral	LD50	500 mg/kg (ATE)
------	------	-----------------

**Primary irritant effect:**

**on the skin:** No irritant effect.

**on the eye:** No irritant effect.

**by inhalation:** No irritant effect expected.

**Sensitisation:**

There are no indications for a sensitising potential of the product. Contains substances with sensitising potential in low concentration (<1%).

**Subacute to chronic toxicity:**

Prolonged and/or repeated contact may cause defatting of the skin which can lead to dermatitis and may make the skin more susceptible to irritation and penetration by other materials.

### SECTION 12: Ecological information

**12.1 Toxicity**

**Aquatic toxicity:** Based on labelling toxic effects are to be expected on aquatic organisms.

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** The product is not soluble in water. If it enters soil, it will adsorb to soil particles and will not be mobile.

**Ecotoxicological effects:**

LC/EC/IC50	10-100 mg/l (seaweed)
	10-100 mg/l (fish)

**Remark:** Harmful to fish.

**Additional ecological information:**

**General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms.

(Contd. on page 8)

GB

# LIEBHERR

# Liebherr-Lubricants

Page: 8/10

## Safety data sheet

according to 1907/2006/EC, Article 31 and 453/2010/EC respectively

Printing date: 23.04.2015

\*\*Version number 2

Revision: 22.04.2015

Trade name: **Liebherr Hydraulic-Gear ATF**

(Contd. of page 7)

### 12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects: No further relevant information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

#### European waste catalogue

13 02 05\* mineral-based non-chlorinated engine, gear and lubricating oils

**Uncleaned packaging:** Empty packing completely. Handover to authorized disposal company.

#### Recommendation:

Disposal must be made according to official regulations.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

## SECTION 14: Transport information

### 14.1 UN-Number

ADR, ADN, IMDG, IATA

Void

### 14.2 UN proper shipping name

ADR, ADN, IMDG, IATA

Void

### 14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class

Void

### 14.4 Packing group

ADR, IMDG, IATA

Void

### 14.5 Environmental hazards:

Marine pollutant:

No

### 14.6 Special precautions for user

Not applicable.

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

(Contd. on page 9)

GB

# LIEBHERR



# Liebherr-Lubricants

Page: 9/10

## Safety data sheet

according to 1907/2006/EC, Article 31 and 453/2010/EC respectively

Printing date: 23.04.2015

\*\*Version number 2

Revision: 22.04.2015

Trade name: **Liebherr Hydraulic-Gear ATF**

(Contd. of page 8)

UN "Model Regulation": -

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulations:

##### Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

**Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

**Department issuing MSDS:** Department of Environmental Protection

#### Contact:

Liebherr-Lubricant-Hotline: +49 (0) 73 54 / 80-6060

E-mail: [lubricants@liebherr.com](mailto:lubricants@liebherr.com)

#### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

(Contd. on page 10)

GB

# LIEBHERR

# Liebherr-Lubricants

Page: 10/10

## Safety data sheet

according to 1907/2006/EC, Article 31 and 453/2010/EC respectively

Printing date: 23.04.2015

\*\*Version number 2

Revision: 22.04.2015

Trade name: **Liebherr Hydraulic-Gear ATF**

(Contd. of page 9)

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

\* Data compared to the previous version altered.

\*\*Information about the version number: Replaces all previous versions.

GB

# LIEBHERR